

Artisan Ring Turning Chuck Instructions

Supplies Needed

- Revolving Center
- Ring Chuck Bushings
- Prepped Ring Blank
- Eye and Ear Protection

Using the Ring Chuck

1. Before using the ring chuck make sure you have followed our instructions on ring turning and have a prepped ring blank.
2. Mount the prepped ring blank on the ring chuck using the bushings. *Note: For 3mm wide cores, sizes 4-7 you may need flip one of the bushings for them to mount securely.*
 - Small Bushings fit rings 4-7
 - Medium Bushings fit rings 8-11
 - Large Bushings fit rings 12-16
3. Once the ring is mounted between the bushings secure them using the knurled brass nut. Bring up a revolving center for support. *See Fig. 1*
4. Turn the blank to your desired shape. Sand the blank through 320 grit or higher.
5. Finish the blank with your choice of finish, we recommend doing a CA finish as it will be glossy and resistant to moisture.
6. Your ring is now ready to wear!

Optional Uses for the Ring Chuck

1. Because the ring chuck is threaded 3/8"x16tpi you can use this chuck for any project kit that has the same thread such as; the bottle opener, pizza cutter, bottle stoppers, coffee scoop, and much more.
2. Using the ring chuck for these other projects is easy, simply use the required project bushing and thread your project blank directly onto the ring chuck and follow your project kit instructions.

Figure 1

